



**INSTALLATION:**

1. TIGHTEN NUTS BY HAND WITH A NUT DRIVER AS SPECIFIED. DO NOT OVERTIGHTEN SINCE STRIPPING WILL RESULT.
2. TIGHTEN 3 TURNS AFTER CONTACT WITH FLAT WASHER.
3. TIGHTEN 1-1/4 TURNS AFTER CONTACT WITH TANK, 10 IN.-LBS. MAX.

**ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE.  
 ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A ± 3% TOLERANCE.**

3	24	34700700	ASM BOLT KIT BOLTED SEALED MANWAY
2	1	35300420	LID PE 24IN MANWAY
1	1	33100131	GASKET PE 24IN SEALED MANWAY
ITEM NO.	QTY.	PART NUMBER	DESCRIPTION
DO NOT SCALE		DRAWN BY	
STATUS: <b>Released</b>		IGG	
© SNYDER INDUSTRIES, INC., 2018			<b>ASM MANWAY PE 24IN SEALED</b>
<small>ALL DIMENSIONS, DESIGNS, AND INFORMATION ON THIS PRINT MUST BE CONSIDERED PROPRIETARY TO SNYDER INDUSTRIES, INC. AND MAY NOT BE USED, COPIED, OR DISTRIBUTED WITHOUT WRITTEN PERMISSION OF AN OFFICER (OR HIS AGENT) OF THE FIRM.</small>			
		(402) 467-5221 www.snydernet.com	PART NO. <b>34700353</b> ENG. ID. <b>D008974</b>
			REVISION <b>A</b> SHEET 1 OF 1