


X



	\neg	г		
		6.2		
42.0	_	A	■	48.0

STANDARD OPEN TOP VAT SIZES - 42" X 48" BASE				
VOLUME		APPROX. OAH DIM "X"		
23 CF	174 G	26.8"		
30 CF	226 G	32.8"		
37 CF	278 G	38.8"		
44 CF	329 G	44.8"		
57 CF	433 G	56.8"		
71 CF	536 G	68.8"		


STANDARD FEATURES:

- 1. SHELL & HEAD CONSTRUCTION OF 10 GA 304SS MATERIAL.
- 2. ALL WELDS ARE CONTINUOUS & CLEANED OF SLAG & SPATTER.
- 3. INTERNAL WELDS ARE GROUND SMOOTH TO A 150 GRIT FINISH.
- 4. FOOT HOLES WELDED SHUT WITH WATER TIGHT WELD & GROUND FLUSH.
- 5. TANKS WILL NOT STACK.

AVAILABLE OPTIONS:

- ALTERNATE MATERIALS OF CONSTRUCTION & FINISHES.
- 7. CUSTOM SIZES/CAPACITIES.
- 8. MULTIPLE FITTINGS TYPES & SIZES.

OUTLET OPTIONS







SANITARY FERRULE W/ CLOSURE

Released

© SNYDER INDUSTRIES, LLC, 2021

ALL DIMENSIONS, DESIGNS, AND INFORMATION ON THIS PRINT MUST BE CONSIDERED PROPRIETARY TO SNYDER INDUSTRIES, LLC, AND MAY NOT BE USED, COPIED, OR DISTRIBUTED WITHOUT WRITTEN PERMISSION OF AN OFFICER (DR HS GAETH) OF THE IRIM.

1005 Atlantic Drive West Chicago, IL 60185 (630)293-0303

www.bonarplastics.com

ASM OT VAT
W/REINFORCMENT BAR 10GA

PART NO.

D011372

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A \pm 3% TOLERANCE.