



NOTES:

1. ALL WELDED CARBON STEEL CONSTRUCTION.
2. STAND TO BE PAINTED BLACK.
3. FOOT PAD HOLES SIZED TO ACCOMODATE 1/2" ANCHOR BOLTS.
4. STAND MUST BE SECURED TO A CONCRETE PAD USING PROPERLY SIZED ANCHORS PRIOR TO ANY LOADING.

***ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.**
***ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.**
***Consult Snyder's Guidelines for Use and Installation prior to delivery.**
Available on-line at <http://www.snyderindustriestanks.com/Technical>
ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE.
ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A $\pm 3\%$ TOLERANCE.

DO NOT SCALE		REVISION	
STATUS:	Released	A	
© TANK HOLDING, CORP, 2026		SHEET 1 OF 1	
 www.tankholding.com			
PART NO.	63932	ENG. ID.	A025960