

*ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.
*ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.
*Consult Snyder's Guidelines for Use and Installation prior to delivery.
Available on-line at http://www.snyderindustriestanks.com/Technical

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A \pm 3% TOLERANCE.

	DO NOT SCALE	DRAWN BY	DATE	OH CHVDER	TITLE:			REVISION
ſ	Released	ET3	07/31/2013	INDUSTRIES, INC.	ASM TK 3000VDT X 90		Α	
ſ	© SNYDER INDUSTRIES INC., 2014			4700 Fremont Street Lincoln, NE 68504			SHEET 1 OF 1	
	ALL DIMENSIONS, DESIGNS, AND INFORMATIC CONSIDERED PROPRIETARY TO SNYDER INDUS BE USED, COPIED, OR DISTRIBUTED WITHOUT WOFFICER (OR HIS AGENT) OF THE FIRM.	TON YAM DI	(402) 467-5221 www.snydernet.com	PART NO	5130100N	D001155		