

\*ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.
\*ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.
\*Consult Snyder's Guidelines for Use and Installation prior to delivery.
Available on-line at <a href="http://www.snyderindustriestanks.com/Technical">http://www.snyderindustriestanks.com/Technical</a>

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A  $\pm$  3% TOLERANCE.

	DO NOT SCALE	DRAWN BY	DATE	CHVDER	TITLE:				REVISION
STATUS:	Released	KB	07/28/2014	INDUSTRIES, INC.	ASN	1 TK 3650	<b>VDT X</b>	102	A
© SNYDER INDUSTRIES INC., 2014				4700 Fremont Street Lincoln, NE 68504					SHEET 1 OF 1
ALL DIMENSIONS, DESIGNS, AND INFORMATION ON THIS PRINT MUST BE CONSIDERED PROPRIETARY TO SNYDER INDUSTRIES, INC. AND MAY NOT BE USED, COPIED, OR DISTRIBUTED WITHOUT WRITTEN PERMISSION OF AN				(402) 467-5221 www.snydernet.com	PART NO. 8190000N ENG. ID. DO			D002	2454